

Parameter	Teileinzugsgebiet												
	1	2	3	4	5	6	7	8	9	10	11	12	13
CN II (90%/0) [-]	85,27	85,41	84,45	86,30	85,44	86,09	85,95	85,68	86,03	85,85	85,82	85,96	85,22
CN II (90%/50) [-]	81,27	81,18	81,74	81,59	82,43	81,19	81,03	81,43	81,16	81,33	81,05	81,17	81,93
CN II (90%/100) [-]	77,28	77,04	79,90	76,92	79,50	76,33	76,26	77,18	76,30	76,82	76,27	76,38	78,64
CN I (90%/0) [-]	71,26	71,49	69,94	72,96	71,55	72,62	72,38	71,94	72,51	72,22	72,17	72,40	71,19
CN I (90%/50) [-]	65,03	64,90	65,73	65,50	66,77	64,91	64,66	65,26	64,87	65,12	64,69	64,88	66,02
CN I (90%/100) [-]	59,31	58,98	63,01	58,81	62,43	58,01	57,92	59,17	57,98	58,68	57,93	58,09	61,20
AV ₀ (90%/0) [mm]	5,12	5,06	5,46	4,71	5,05	4,79	4,85	4,95	4,82	4,88	4,90	4,84	5,14
AV ₀ (90%/50) [mm]	6,83	6,87	6,62	6,69	6,32	6,87	6,94	6,76	6,88	6,80	6,93	6,88	6,54
AV ₀ (90%/100) [mm]	8,71	8,83	7,46	8,89	7,64	9,19	9,23	8,76	9,20	8,94	9,22	9,16	8,05
B1 (90%/0) [-]	42,98	43,19	41,84	44,60	43,24	44,26	44,02	43,60	44,15	43,87	43,83	44,05	42,92
B1 (90%/50) [-]	38,25	38,16	38,71	38,56	39,42	38,17	38,01	38,40	38,15	38,31	38,03	38,15	38,90
B1 (90%/100) [-]	34,99	34,82	37,01	34,74	36,67	34,35	34,30	34,92	34,33	34,67	34,31	34,38	35,98
VN21 [-]	10,94	11,74	11,10	11,70	11,70	11,19	11,27	11,27	11,27	11,35	13,47	10,60	11,19
AV (90%/0) [mm]	3,97	3,86	4,19	3,62	3,85	3,72	3,75	3,83	3,73	3,77	3,60	3,81	3,96
AV (90%/50) [mm]	5,13	5,05	4,97	4,94	4,70	5,12	5,16	5,04	5,12	5,06	4,87	5,21	4,90
AV (90%/100) [mm]	6,37	6,30	5,52	6,35	5,56	6,64	6,64	6,35	6,63	6,45	6,23	6,73	5,90